



Philips TUV T5

Lamptype	Driver	12nc	USA	Europe /Asia	Only suitable for <8 switches per day*	Lamps on Driver
TUV 24T5 HE	ICN255490CN	913701246102	X			2
	ICN255490CN	913701246102	X		X	1
	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266		X		1
	HF-P 154/155 TL5 HO/PLL III 220-240V IDC	913713028266		X		1
TUV 24T5 HO	IUV2S60M4LD	913710260202	X	X	X	1
TUV 36T5 HE	ICN255490CN	913701246102	X		X	1
	ICN255490CN	913701246102	X			2
	ICN2554T	913701253302	X			2
	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266		X		1
TUV 36T5 HO	IUV2S60M4LD	913710260202	X	X	X	1
TUV 48T5 HE	ICN255490CN	913701246102	X		X	1
	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266		X		1
	HF-P 154/155 TL5 HO/PLL III 220-240V IDC	913713028266		X		1
TUV 48T5 HO	IUV2S60M4LD	913710260202	X	X	X	
TUV 64T5 HE	HF-P 180 TL5 III 220-240V	913713034266		X	X	1
	ICN255490CN	913701246102	X		X	1
TUV 64T5 HO	IUV2S60M4LD	913710260202	X	X	X	1

*Driver is suitable tested on 2 3/4h ON - 1/4h OFF switching schedule